

WOODS **BATWING™** BW240 ROTARY CUTTERS & BW240HD ROTARY CUTTERS

20-FOOT FOLDING-WING ROTARY CUTTER



BW240 shown with chain shielding.



on both
BW240 & BW240HD



on
BW240



on
BW240HD

Introducing the Woods' Batwing™ BW240 and BW240HD folding wing cutters—two brand new cutters providing the means to match the ways.

The Woods BW240 and BW240HD 20-foot rotary cutters—versatile, rugged, and built to handle a host of applications. Solid performers, these triple-spindle cutters meet the individual challenges they're designed to handle—be it simple grass mowing or cutting brush up to 3-inches in diameter. No longer do users have to buy more cutter than they need. The BW240 is in a class of its own. The BW240HD matches the best of the best. Both provide an economical choice when matching the right cutter with the right application.

Both Batwings provide excellent floatation on soggy grounds while improving such floatation with the use of dual wheels on the center section (standard) and wing sections (option). Engineered to be pulled by utility size tractors with 70 or more horsepower, the BW240 can also be pulled by tractors up to 160 PTO, while the BW240HD can be pulled by tractors up to 200 PTO.

Along with a deck rust-through warranty and gearbox warranty that's second to none, Woods proves once again why users view us as the attachment experts.

FEATURES

- Smooth, sloped top deck sheds water and debris
- 13.25-inch side frame depth; deepest in the industry
- Unique wing shape; for lower tongue weight and improved trimming

BW240 PERFORMANCE GUIDE

Ideal for grassy fields, pastures, waterways and brush up to 2-inches in diameter.

BW240HD PERFORMANCE GUIDE

Ideal for utility mowing, heavy grass and weeds, waterways, ditches and brush up to 3-inches in diameter.



- Bolt-on skid shoes with "approachable" leading edge
- Internal baffling in each deck for even distribution of material
- Greaseable pivot points on turnbuckle and axle arms
- Full length, 1-inch wing hinge pin
- 10-Year Deck Rust-Through Warranty
- 6-Year (BW240) and 7-Year (BW240HD) Gearbox Warranty (Limited)
- Full length replaceable "bolt-on" skid shoes
- Woods Exclusive quick-change blade pins
- Operator's manual container
- Standard spring wheel yoke arms
- Meets AWS® Certification welding standards

WOODS
The Attachment Experts.™

WOODS® BATWING BW240 ROTARY CUTTERS

Specifications	240 / 240HD	240 / 240HD
Capacity		
Cutting Swath, in.	240	
Cutting Height, in.	2 to 15	
Cutting Capacity (dia.) in.	2 / 3	
Side Frame Depth, in.	13.25	
Tractor Compatibility		
Tractor PTO HP Range	70 to 160 / 70 to 200	
Tractor PTO (RPM)	540 or 1000	
Static Vert Drawbar Load lb.	2400 w/chains	
Hitch	Pull type, self level clevis	
Dimensions		
Transport Width, in.	123	
Overall Width/Length, in.	250/198	
Deck Type	Smooth, Sloped	
Deck Thickness	0.135	
Side Frame Thickness, in.	0.25	
Hinges	Continuous	
Approx. Weight, lb.	6510 / 6600 lbs. w/chains	
Drivelines		
Main	Cat. 6 CV or Cat 5 Hvy 3 joint	
Connecting	Cat. 4 Telescoping Profile	
Gearcases		
Number	4	
Vertical Shaft Size, in.	2 / 2.38	
Splitter HP (Spindle HP)	160 (120) / 235 (190)	
Blades		
Thickness, in.		1/2
Width, in.		4
Type		Hi-lift
Overlap, in.		6
Blade Tip Speed, ft./min.		
540 RPM		15,450 FPM
1000 RPM		16,300 FPM
Material Flow System		
		Standard Baffles
Stump Jumper/Type		
		Standard/Round Welded
Hydraulics		
Wing Flex, degrees		90 up, 22 down
Wheels Type		
Option 1		Laminated
Option 2		24" Aircraft
Option 3		24" Foam Filled Aircraft
Option 4		29" Aircraft
Option 5		Wheels Less Tires
Spring Suspension		
		Standard
Wing Leveling Adjustment		
		Easy Adjust Turnbuckle
Shielding		
Front		Rubber Belting or Chain
Rear		Rubber Belting or Chain
Gearbox Warranty		
		6 Year / 7 Year
Deck Rust Through Warranty		
		10 years

"Bolt-on" skid shoes with "approachable" leading edge



Replaceable and reduces sod damage when turning.

Smooth, sloped top deck




Sheds water and debris to prevent rust and corrosion.

Exclusive "quick-change" blade system



Woods' exclusive "quick-change" blade system allows for easy changing of blades.

Greasable pivot points



Located on turnbuckle and axle arms increase durability and reduce wear.

WOODS

The Attachment Experts.™

Woods Equipment Company 2606 South Illinois Route 2, PO Box 1000, Oregon, Illinois 61061 tel 800-319-6637 www.WoodsEquipment.com

WARNING! Some images may show safety shields removed to provide a better view. Equipment should never be operated without required safety equipment. Always operate machines in accordance with supplied operator's manuals. Some machines in this brochure may be shown with optional equipment. Specifications subject to change without notice. Woods, the Woods logo, Batwing, "The Attachment Experts.", and WoodsCare are trademarks of Woods Equipment Company. All other trademarks, trade names, or service marks not owned by Woods Equipment Company that appear in this brochure are the property of their respective companies or mark holders.

© 2008 Woods Equipment Company. All rights reserved. B-02081B (REV. 0808)